



FST™ Floating Sub Tool

Volant’s FST™ tool is designed for casing drilling or running operations with top drive equipped rigs to supply passively damped axial travel during connection making. The FST tool helps to prevent damage due to jarring or sudden loading to casing or drilling equipment during day-to-day operations.

This patent pending architecture is capable of providing full hoisting loads in combination with full torque values at all stroke positions. The FST tool is fully compatible with Volant’s CRTi® tool with internal grip and CRTe® tool with external grip.

Base Tool Characteristics

Tool Weight	lbs (kg)	860 (391)
Maximum Hoist Load ¹	ton (tonne)	660 (598)
Maximum Torque Capacity ¹	ft.lbs (N.m)	85,000 (115,200)
Collapsed Tool Length ²	in. (mm)	42.0 (1,070)
Tool Stroke ^{3,4}	in. (mm)	6.0 (150)
Extended Tool Length ²	in. (mm)	48.0 (1,220)
Maximum Tool Diameter	in. (mm)	12.25 (311.5)
Maximum Circulation Pressure	psi (MPa)	7,500 (51.7)
Through Hole	in. (mm)	2.0 (50)
Maximum Compressive Load	ton (tonne)	270 (244)
Tool Joint		6-5/8 REG

Extended

Collapsed



1. Tool hoist and torque ratings are based on API Specification 8C, and are valid for any combination of torque and hoist. The rated capacity does not take into account any limitations that may result from the tool joint connection.
2. This does not include the length of the crossover or saver sub, which is recommended for use with the FST-2.
3. Additional tool stroke can be provided on request at the expense of tool length.
4. An optional passive compensator system is available by request.

*Volant® is a registered trademark of Volant Products Inc. CRTi®, CRTe® and FST™ are trademarks of Noetic Technologies Inc.

